

# CIMAGE K300 - K400



FOR THERMAL PRINTERS



**DESIGNED  
FOR**

- CLUBS/ASSOCIATIONS**
- INSURANCE COMPANIES**
- PRIVATE ORGANISATIONS**
- RETAIL STORES**
- HOTELS**
- SERVICE BUREAUX**
- AMUSEMENT PARKS**
- FAST FOOD OUTLETS**
- PUBLIC ADMINISTRATION**
- TRANSPORT COMPANIES**
- BANKS/CREDIT INSTITUTIONS**

## PRODUCING QUALITY HAS BECOME VERY EASY

The K300 Optima and the K400 Optima provide solutions for thermographic printing on plastic cards. Choose from a range of options such as integrated Hi-Co/Lo-Co encoding, chip encoding, and watch your designs come to life, quickly and effortlessly.





## CIMAGE K300 - K400 Optima

The CIMAGE K300 Optima and K400 Optima provide high performance printing that is also friendly!

- ✓ A fast 32 bit processor and 300 DPI print resolution ensure efficient, quality printing in colour or monochrome.
- ✓ An injection moulded polycarbonate frame together with a new cleaning cartridge design ensure maximum reliability and long life.
- ✓ A completely closed input hopper guarantees clean, quality results every time.
- ✓ For added convenience the K300 and K400 Optima also come with a brand new flip-over unit in ABS, a reject box and a user friendly LCD display.

The CIMAGE K300 Optima and K400 Optima - the undisputed winners in their class.



### Technical Features

CIMAGE K-SERIES	K300 Optima	K400 Optima
<b>Technology</b>	Colour Dye Sublimation/Resin	Colour Dye Sublimation/Resin.
<b>Print resolution</b>	300 DPI.	300 DPI.
<b>Printing speed</b>	144 CPH in full colour. 1000 CPH in monochrome.	35 seconds in full colour (one side).
<b>Bar Codes</b>	2/5, CODE 39, EAN 128 UPC-A, PDF-417	2/5, CODE 39, EAN 128 UPC-A, PDF-417
<b>Card materials</b>	ABS, PVC and Polyester.	ABS, PVC and Polyester.
<b>Card thickness</b>	From 0.4 to 1.5 mm.	From 0.4 to 1.5 mm.
<b>Power supply</b>	120V - 240V A.C. 50-60 Hz	120V - 240V A.C. 50-60 Hz
<b>Operating temperature</b>	5°C + 35°C.	5°C + 35°C.
<b>Dimensions (WxDxH)</b>	320 x 245 x 232 mm.	410 x 245 x 232 mm.
<b>Weight</b>	7 Kg.	8,4 Kg.
<b>Interface</b>	Serial and parallel port.	Serial and parallel port.
<b>Magnetic encoding</b>	Optional: Lo-Co and Hi-Co.	Optional: Lo-Co and Hi-Co.
<b>Chip initialisation</b>	Optional.	Optional.
<b>Multi-thickness feeding</b>	Standard.	Standard.
<b>Front-rear print FLIP-OVER</b>	No.	Yes.
<b>Memory extension</b>	2 MB Standard.	4 MB Standard.
<b>Windows drivers</b>	Win95, Win98, WinNT, Win2K, WinXP.	Win95, Win98, WinNT, Win2K, WinXP.
<b>Models</b>	K300C/CM/CE/CEM Monochrome K300/M/E/EM	K400C/CM/CE/CEM

\*Data subject to change without notice.

### YOUR REPRESENTATIVE

DESIGNED FOR

CLUBS/ASSOCIATIONS, INSURANCE COMPANIES,  
PRIVATE ORGANISATIONS, RETAIL STORES, HOTELS,  
SERVICE BUREAUX, AMUSEMENT PARKS,  
FAST FOOD OUTLETS, PUBLIC ADMINISTRATION,  
TRANSPORT COMPANIES, BANKS/CREDIT INSTITUTIONS



THE PERSONALITY WRITER  
CARD PRINTERS AND EMBOSsing PRODUCTS

CIM S.p.A. - Via O. Serra 2, 40012 Calderara di Reno BO, Italy  
Tel. +39 051.64.65.011 Fax +39 051.64.65.012 [info@cimitaly.it](mailto:info@cimitaly.it) [www.cimitaly.it](http://www.cimitaly.it)